Fastmark M9XPd

Easy Implementation and Easy to Use for All-Around Thermal Printing



PAL®: The AMT Datasouth Difference

Implementation is made easy with our plug and play capability - saving the IT team time and effort. In addition to popular emulations, our proprietary PAL® programming language resides in the smart printer allowing us to load an app that will accept your data stream and convert, format and print to fit your organization's requirements, including both linear and 2D barcodes. You can unplug any existing printer and replace it with the Fastmark® M9XPd. And, ongoing service and support, including future changes to the PAL® app, if needed, are available for the life of the printer.

- Easy to use touchscreen interface
- Print speeds up to 12 ips
- Highest quality barcodes
- 203 and 300 dpi models available
- Our powerful and versatile "PAL"
- Equipped with popular emulations





The M9XPd is ready for loading custom PAL® applications



PRINTER SPECIFICATIONS INCLUDE:

Printer Model Fastmark M9XPd

Resolution 203, 300 dpi

Printer Language PAL®, Compatible to ZPL, EPL, DPL

Printing Method Direct Thermal/Thermal Transfer

Print Speed Up to 12 ips - 203 dpi Up to 9 ips - 300 dpi

Max Print Width 4.21 inches - 203 dpi

4.16 inches - 300 dpi

Media Width 0.8" - 4.7"

Max Length 1000 inches – 203 dpi

450 inches – 300 dpi

Media Outside

Diameter 8.0"

Media Thickness 2.36 - 11.0 mil

Dimension (W) 9.8" x (D) 17.2" x (H) 10.8"

Weight 20 lbs

Display Touch Color LCD

Sensors Gap transmissive, black bar reflective

Memory 256MB DRAM/SDRAM 256MB Flash ROM

Processor 32-bit

Interfaces RS-232, USB, USB HOST,

Ethernet

Optional: GPIO, Bluetooth, WiFi 802.11 b/g/n (slot adapter)

Barcodes Linear and 2D

Ribbon Core 1"

Ribbon Outside 3.2"

Diameter

Ink coated inside/outside

Cutter User Option

Real Time Clock Standard

Limited Warranty Printer: 2 years

Print Head: 1 year

Agency CB, FCC Class A, CE Class A,

cTUVus, TÜV, ENERGY STAR®



