

Fastmark® ZY15

Compact Desktop Thermal Bar Code Printer



The Fastmark ZY15 is a strong printer at an affordable price point.

It is capable of printing thermal transfer and/or direct thermal media. At 203 dpi the ZY15 has a print width over 4 inches wide, handling up to a 5" diameter media supply. This printer is an ideal solution for a variety of applications, including healthcare (downtime management and patient identification), retail, inventory, process control, or shipping.

Fastmark ZY15 – The economical choice for barcode printing



PRINTER SPECIFICATIONS INCLUDE:

Resolution	203 dpi
Printing Method	Direct Thermal and Thermal Transfer
Print Specifications	6 ips (max), 4.25" Width, 1000" length
Physical	8.03" (W) x 6.46" (H) x 11.02" (D), 5.29 lbs
Label Roll Capacity	5 inches (outside diameter)
Ribbons	OD 67 mm, 1" core (ink coated outside) OD 40 mm, 0.5" core (ink coated outside)
Processor	32-bit RISC CPU
Memory	128 MB Flash memory 64 MB SDRAM
Interfaces	USB 2.0 Internal Ethernet, 10/100 Mbps RS232 USB host, for scanner or PC keyboard Internal Bluetooth 4.0 (Factory option) External Bluetooth (user option)
Sensors	Transmissive gap Black mark reflective Head open Ribbon end
Internal Fonts	8 alpha-numeric bitmap fonts Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Real Time Clock, Buzzer	Standard
Options	Peel-off module Guillotine cutter (full cut and partial cut)

Bar Code 1D bar code

Code 128UCC, Code 128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code 11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS

2D bar code

GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417

Font and Barcode Rotation

0, 90, 180, 270 degree

Command Set

Compatible to EPL, ZPL, ZPL II, DPL

Media Type

Continuous, die-cut, black mark, fan-fold, notched (outside wound)

Media Width

0.8" ~ 4.4"

Media Thickness

2.36 ~ 7.48 mil

Media Core Diameter

1" ~ 1.5"

Label Length

0.2" ~ 1000"

Agency

FCC Class B, CE Class B, C-Tick Class B, UL, cUL, TÜV/safety, CCC, EAC, CoC, BIS, KC, Energy Star®

Environmental

Comply with RoHS, REACH, WEEE

Limited Warranty

Printer: 2 years
Print Head: 1 million inches or 12 months whichever comes first
Platen: 2 million inches or 12 months whichever comes first

*All information subject to change without notice and is protected by AMT Datasouth copyright.

AMTDatasouth

Corporate Headquarters

3222 Corte Malpaso
Suite 208
Camarillo, CA 93012
800-215-9192 PH



Charlotte Operations

5033 Sirona Dr., Suite 800
Charlotte, NC 28273
800-476-2120 PH

www.amtdatasouth.com

Printers backed by AMT Datasouth's quality guarantee.