

Fastmark M3 Series

Ideal Battery Powered Portable Printer

Fastmark M3 – Fast print speed and lasts up to 12 hours on a single charge

The Fastmark M3 is a lightweight compact mobile printer ideally suited for a wide variety of mobile applications from receipts to barcode labels. Couple the Bluetooth version with a Bluetooth scanner for the perfect patient bedside specimen label solution. Our PAL programming language makes the Fastmark M3 an intelligent printer allowing customization of output.

Standard Features

- PAL Plus TSPL-EZ (EPL and ZPL emulations)
- Full 3" width media
- USB, Bluetooth or WIFI interfaces, optional RS-232
- 203 dpi printhead resolution
- Print speeds up to 4 ips
- Easy media loading
- Optional vehicle power adapter
- Belt clip and shoulder strap options
- Direct thermal printing on all popular media material
- 2 year warranty



AMTDatasouth

PALSM
It speaks your language 

All M3s are ready for loading custom PAL applications



PRINTER SPECIFICATIONS INCLUDE:

Printer Model	Fastmark M3	Interfaces	USB and 802.11b/g/n WiFi or USB and Bluetooth Optional RS-232
Resolution	203 dpi	Linear Bar Codes	Code 39, Code 93, Code128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GSI Data Bar
Command Set	PAL Plus and TSPL-EZ (EPL and ZPL emulations)	2D Bar Codes	PDF-417, Maxicode, Data Matrix, QR Code, Aztec
Printing Method	Direct Thermal	Windows compatibility	Win CE, NET, Pocket PC, Windows Mobile2002/2003SE, Windows 2000/XP/Vista/Win 7
Print Speed	Up to 4 ips	Battery	Rechargeable 7.4V DC 2500 mAh Li-on two-cell battery, Operating 12 hours
Max Print Width	2.83 inches	Standard items	Belt clip, AC adapter, single battery charger, cleaning pen, sample receipt roll, Quick Guide
Max Print Length	90 inches	Options	Shoulder strap, Environment case, Spare Battery, 1 bay Battery charger, Vehicle power adapter
Media width	1.0" – 3.0"	Power	Input: AC 100-240V, 50 – 60Hz 12 VDC 1.25 A output
Media Core diameter	.4" to 1"	Environment Conditions	Operation: 14 – 122 F, 10 – 90% non-condensing Storage: -40 – 140 F, 10 – 90% non-condensing
Label Roll Capacity	2.25" OD – receipts, 2.16" OD labels	Warranty	Two years
Media Types	Labels, receipt paper, continuous, die-cut, tag, notch, black mark (on printable side)	Agency Approval	CE Class B, FCC, CB, CCC, C-Tick
Sensors	Reflective (gap, black mark) head open		
Enclosure	Plastic with rubber over-mold construction 3 buttons (On/Off, Feed, Cover Release) 2 color LED's for printer status 3 LED's for battery status Clamshell design with Belt clip or shoulder strap		
Physical Dimension	2.75" (D) x 4.57" (W) x 5.83" (H) Weight 1.2 lbs with battery		
Processor	32-bit RISC CPU		
Memory	4MB Flash 8MB SDRAM		

AMTDatasouth

Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, California 93012
(805) 388-5799 PH
(805) 484-5282 FX

www.amtdatasouth.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH
(704) 525-6104 FX

Part No. 120331 rev. A
Specifications are subject to change without notice.
#16487

PAL
It speaks your language

The PAL logo consists of the letters 'PAL' in a bold, blue, sans-serif font. To the right of the text is a stylized illustration of a parrot with blue, yellow, and red feathers. Below the parrot is a small graphic of a speech bubble containing the letters 'tj'.